

ILS or LOC RWY 3

LOC I-COF 109.1	APCH CRS 027°	Rwy Idg TDZE Arpt Elev 9008 5 8	AL-38 [USAF]
DME required			PATRICK SFB (KCOF)

▽ * When ALS inop, increase RVR to 40 and vis to ½ mile.
****** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile;
 CAT CD vis to 1½ miles.
******* Circling not authorized NW of Rwy 3-21. When Rwy 29 VGSi inop, circling to Rwy 29 NA at night. When circling to Rwy 29 at night, operational VGSi required, remain on or above VGSi glidepath until threshold.

ATIS ★ 119.175 273.5	ORLANDO APP CON 132.65 281.425	TOWER ★ 133.75 269.375	GND CON 124.35 335.8
			CLNC DEL 118.4 289.4

1046
▲

ELEV 8	TDZE 5
Rwy 29 Idg 3687'	HIRL Rwy 3-21 MIRL Rwy 11-29

EMERG SAFE ALT 100 NM 3000

CATEGORY	A	B	C	D
S-ILS 3 *	205/24		200	(200-½)
S-LOC 3 **	460/24	455 (500-½)	460/45	455 (500-¾)
CIRCLING ***	520-1	512 (600-1)	540-1½ 532 (600-1½)	560-2 552 (600-2)